

# >Disolvente de extracción



Physical state: Liquid

Color: Colorless

Odor: Characteristic

PH value: Not applicable. Change in condition

Melting point / Melting range: Undetermined.

Boiling point / Boiling range: 60 - 120 ° C

Flash point:> 7 ° C

Auto-ignition temperature: 310°C

Danger of explosion: Product is not explosive. However, formation of explosive air / vapor mixtures are possible

**Application:** The extraction solvent is a colorless liquid with a characteristic odor. It is used industrially as a base solvent, raw material for the production of other solvent compositions used in the paint and varnish industry.

## VARIATIONS

**Image****Price**

£123,50 gross | £100,41 netto

**Pack size**

200 L

## PRODUCT DESCRIPTION

### Disolvente de extracción

The extraction solvent is a colorless liquid with a characteristic odor. It is used industrially as a base solvent, raw material for the production of other solvent compositions used in the paint and varnish industry.

Physical state: Liqui

Color: Colorless

Boiling point: 60-120 ° C

Flash point:> 7 ° C

Density at 20 ° C: 0,690 – 0,780 g/cm<sup>3</sup>

Water solubility: Not miscible. Hazard pictograms

Labels for hazardous chemicals and mixtures that are part of the Globally Harmonized System of Classification and Labeling of Chemicals (GHS). The pictograms recommended by GHS have the shape of a square set on the top. They should contain a black symbol on a white background with a red border.

Priority rules to be observed in connection with the labeling of a substance:

- the skull and crossbones, the exclamation mark pictogram should not be added.

- corrosivity, the pictogram exclamation mark should not be added if it concerns eye or skin irritation.
- health hazard determining respiratory sensitization, the exclamation mark pictogram should not be added if it concerns skin sensitization or irritation to eyes or skin.

Source: [GHS pictograms](#)