



CAS number: **79-20-9** 

Summary formula: C3H6O2 Molar mass: 74.08 g / mol

Synonyms: acetic acid methyl ester Translation [ENG]: methyl acetate

Application: Methyl acetate is used as a solvent for varnishes, resins, oils and nitrocellulose; paint removers; as a flavoring; and in the production of artificial leather. Solvent for nitrocellulose, cellulose acetate and many resins and oils; artificial leather production.

## **VARIATIONS**

Image	Price	Pack size
$O$ $O$ $CH_3$	£132,81 gross   £107,98 netto	200 L

## **PRODUCT DESCRIPTION**

Methyl acetate 90% [79-20-9]



Methyl acetate is used as a solvent for varnishes, resins, oils and nitrocellulose; paint removers; as a flavoring; and in the production of artificial leather. Solvent for nitrocellulose, cellulose acetate and many resins and oils; artificial leather production.

Boiling point: 56 - 58 ° C (1013 hPa) Density: 0.93 g / cm3 (20 ° C) Explosive limits: 3.1 - 16% (V) Flash point: -13 ° C

Auto-ignition temperature: 455 ° C

Melting point: -98 ° C

Vapor pressure: 217 hPa (20 ° C) Density (d 20 ° C / 4 ° C): 0.932 - 0.934

Solubility: 250 g / l

## **Hazard pictograms**

Labeling of hazardous chemicals and mixtures that are part of the Globally Harmonized System of Classification and Labeling of Chemicals (GHS). The pictograms recommended by GHS have the shape of a square set on the top. They should contain a black symbol on a white background with a red border.

Priority rules to be observed in connection with the labeling of a substance:

- the skull and crossbones, the exclamation mark pictogram should not be added.
- corrosive effect, the exclamation mark pictogram should not be added if it concerns eye or skin irritation.
- health hazard determining respiratory sensitization, the exclamation mark pictogram should not be added if it concerns skin sensitization or irritation to eyes or skin.

Source: **GHS** pictograms